

WCR4000-Series
Hydraulic Torque Wrench

The new WCR4000 combines power and durability with a slim spanner design to provide bolting professionals with one of the most versatile and high performing limited access tools on the market today.



Ideal for bolting API flanges, the WCR4000 is available with a wide range of ring type spanners.

Get into tight spaces and out again, safely, with the new WCR4000-Series hydraulic torque wrench from Enerpac.



ENERPAC®

WCR4000-Series, Benefits and Features

The WCR4000 helps resolve narrow clearance restrictions in bolting of API flanges.

Resolves Bolt to Pipe Restrictions





Reduces Bolt Height Restrictions


W4000 drive unit is compatible with standard W-Series cassettes

Solid steel tool body for maximum endurance and minimum downtime





Tool geometry provides functionality on nearly any API flange.



SAFE-LINK spanner design includes a mechanical fuse inside the cassette, providing a safer bolting experience for the operator and bystanders.



Slim ring style profile provides the ultimate mixture of versatility and durability.*

Model Number	Description	Unit Wt. (lbs)	Unit Wt. (kg)
WCR4000	Roller Cassette Assembly	14.0	6,3
W4000	Torque Wrench Drive Unit	4.4	2,0

Spanner Model Number	Description	A/F Size (in)	A/F Size (mm)	Spanner Radius** (in)	Spanner Radius** (mm)	Unit Weight (lbs)	Unit Weight (kg)
W4107CS	WCR4000 1 7/16 A/F Closed Spanner	1 7/16	36	1.22	31	4.2	1,9
W4108CS	WCR4000 1 1/2 A/F Closed Spanner	1 1/2	38	1.29	33	4.4	2,0
W4110CS	WCR4000 1 5/8 A/F Closed Spanner	1 5/8	41	1.29	33	4.2	1,9
W4113CS	WCR4000 1 13/16 A/F Closed Spanner	1 13/16	46	1.4	36	4.3	1,9
W4114CS	WCR4000 1 7/8 A/F Closed Spanner	1 7/8	48	1.51	38	4.7	2,1
W4200CS	WCR4000 2 A/F Closed Spanner	2	50	1.51	38	4.2	1,9
W4203CS	WCR4000 2 3/16 A/F Closed Spanner	2 3/16	55	1.62	41	4.3	2,0
W4206CS	WCR4000 2 3/8 A/F Closed Spanner	2 3/8	60	1.77	45	4.6	2,1
W4209CS	WCR4000 2 9/16 A/F Closed Spanner	2 9/16	65	1.84	47	4.6	2,1
W4212CS	WCR4000 2 3/4 A/F Closed Spanner	2 3/4	70	1.95	50	4.7	2,1
W4215CS	WCR4000 2 15/16 A/F Closed Spanner	2 15/16	75	2.05	52	4.6	2,1
W4302CS	WCR4000 3 1/8 A/F Closed Spanner	3 1/8	80	2.18	55	4.9	2.2

* Width of spanners = 1.18" (30 mm)
** Radius measured from center of bolt

WCR4000

- Resolves bolt to pipe restrictions
- Reduces bolt height restrictions

e-mail: info@enerpac.com
Internet: www.enerpac.com

Your Enerpac Distributor:

03-070123113 675 US © 2013 Enerpac - Subject to change without notice.

ENERPAC
POWERFUL SOLUTIONS. GLOBAL FORCE.